



ROBTAPE

R4

VERSION: 160822
Page:1/2

MASKING TAPE

DEFINITION

Professional automotive masking tape. Resists temperature up to 80°C (30 min). Does not leave adhesive traces when removed.

CHARACTERISTICS

Backing:	58 g/m ² natural saturated crepe paper
Color:	White
Adhesive:	Natural rubber
Total thickness:	0.125 mm
Adhesion to Steel:	4.5 N/25mm
Tensile strength MD:	85 N/25mm
Elongation at break:	8.0 %
Temp. Resistance:	80°C (30min)

APPLICATION

Masking tape for car repair applications when temperature does not exceed 80°C.

Features	Benefits
Natural rubber and resins solvent based adhesive	<ul style="list-style-type: none">✓ Easy removal without adhesive residue✓ Good adhesion even on irregular surfaces✓ Easy to stick✓ Heat resistant up to 80°C (30 min)
Saturated paper backing	<ul style="list-style-type: none">✓ Compatible with most common paints and lacquers✓ Good conformability to shaped surfaces✓ Removable without breaking

PRODUCT LIFE AND STORAGE

Product shelf life and storage: 12 months; suggested storage temperature from 15°C to 25°C with max. relative humidity of 60%. Material shall be stored away from heat sources and possibly kept in original package. Try to avoid direct sun light exposure.

For any technical information contact with our Customer Attention Service or our Technical Department.
ROBERLO SA declines any responsibility due to an incorrect use of the product.