



AIRCOLOR KLAREX clear coat 1k

H36

VERSION: 230531
Page: 1/2

CLEAR COAT 1K

DEFINITION

AIRCOLOR KLAREX CLEAR COAT 1K is a fast drying, high gloss, U.V.-resistant clear coat, applicable for all standard base coats. Easy to polish, very good flow, ideally suited for Spot Repair's. It can be applied either for spot repairs or can be used for refinishing complete parts.

AIRCOLOR KLAREX CLEAR COAT 1K has a transversal nozzle allows the direction of application to be adjusted by the output nozzle (horizontal/vertical).

PHYSICAL CHARACTERISTICS

Nature:	Thermoplastic acrylic resin
Propellant:	DME
Colour:	Transparent
Specific weight:	0,79 kg/l a 20°C
Shine (60°C):	>80%
Yield:	2 m ² /spray
Dry film thickness:	15-20 μ/coat (2 coats)
Resistance of the container to heat:	< 50 °C
Resistance of paint to heat:	150°C
VOC:	671 g/l Application 2004/42/EC - IIB (e)(840)

SURFACE PREPARATION

30 minutes flash off is required between the basecoat and **AIRCOLOR KLAREX CLEAR COAT 1K** application. Not suitable for recoating water-based paints.

APPLICATION

DRYING TIMES

Nozzle kind: Transversal White /Yellow	2'	20-25 cm	2-3 coats 50 μ	2-3'

20°C	5'-10'	10'-20'	24h	24h
60°C	-	-	40'	40'

REMARKS

Shake the aerosol before use for 2 minutes after hearing the sound of steel mixing balls.
Protect the areas that do not need to be painted.
Drying time depends on temperature, humidity as well as the film thickness applied.
It is not recommended to apply on oil based paints.

EQUIPMENT CLEANING



After use, turn
can upside
down and
spray for
several
seconds

SAFETY

Follow instructions on the product label. For more information check the Safety Data Sheet. Compliant with the National Statutory Regulation for Health and Safety at Work and Waste Disposal.

STORAGE

Store the product in a ventilated place far from direct exposure to sunlight. Keep between +5°C and +30°C.

SHELF LIFE

One year in unopened original packaging.

These products are for professional use only. The Safety Data Sheet should be consulted before use and the precautionary warnings on the product packaging should be observed. Its correct use, according to its purpose and respecting its technical and security data, provided in these documents, is the sole and exclusive responsibility of the user. ROBERLO S.A.U declines any liability due to the incorrect use of any product.

The information included in this documentation is based on our scientific and technical knowledge on the date of its issuance. ROBERLO S.A.U reserves the right to modify and/or discontinue all or part of the information at any time and without prior notice. It is the user's responsibility to verify the update of the information. The latest version of this document replaces all previous versions.

*All clauses contained herein apply to any future changes or modifications.
For any additional technical information please consult with our Customer Service or our Technical Department.*