



# AIRCOLOR CROM acrylic paint white

## H37

VERSION: 230531  
Page:1 /2

### ACRYLIC PAINT



#### DEFINITION

**AIRCOLOR CROM ACRYLIC PAINT WHITE** is a high-quality acrylic paint with a satin finish, suitable for fast industrial painting. Thanks to its professional spray application, it is also suitable for large surfaces. Extremely high pigmentation and specific additives provide high covering power, reduced dripping and good adhesion directly to metal. Product suitable for both partial repairs and patches.





#### PHYSICAL CHARACTERISTICS

<b>Nature:</b>	Thermoplastic acrylic resin
<b>Propellant:</b>	DME
<b>Colour:</b>	White
<b>Specific weight:</b>	0.86 kg/l at 20°C
<b>Brightness (60°C):</b>	>70% Bright
<b>Coverage:</b>	2.5 m <sup>2</sup> /aerosol
<b>Dry film thickness:</b>	15 µ/layer
<b>Heat resistance of container:</b>	< 50 °C
<b>Heat resistance of paint:</b>	120°C
<b>VOC:</b>	664 g/l    Application 2004/42/EC - IIB (e)(840)






#### SURFACE OR SUBSTRATE PREPARATION

PROCESS		OEM paint	Primer
	P360	✓	✓
	DA93	✓	✓

#### APPLICATION

			
2	20-25 cm	2-3 coats	5

#### DRY


				
20	10-15	30	1	15

(\*) To increase the degree of gloss and improve resistance to petrol, it can be repainted after approx. 15 min. (20°C) drying with 1K Varnish.

### NOTES

Shake the aerosol for 2 minutes before use after hearing the mixer noise.  
Do a test coat. Check the colour.  
Drying time depends on the ambient temperature, humidity and thickness of the coat applied.

### EQUIPMENT CLEANING



### SAFETY

Consult the product label. For further information, consult the safety data sheet. Comply with occupational health and safety guidelines and waste disposal regulations.

### STORAGE

Keep in a cool, well-ventilated place, avoiding direct exposure to sunlight. Store between +5°C and +30°C.

### SHELF LIFE

One year in unopened original packaging.

These products are for professional use only. The Safety Data Sheet must be consulted before use and the precautions on the product packaging must be observed. Correct use in accordance with its intended purpose and in compliance with the technical and safety data provided in these documents is the sole responsibility of the user. ROBERLO S.A.U. accepts no liability for the incorrect use of any product.

The information contained in this documentation is based on our scientific and technical knowledge at the time of publication. ROBERLO S.A.U reserves the right to modify and/or discontinue all or part of the information at any time without prior notice. It is the user's responsibility to check that the information is up to date. The latest version of this document replaces all previous versions.

All clauses included in this document are applicable to any future changes or modifications.  
For any additional technical information, please consult our Customer Service or Technical Department.