

1K Plastic Primer Spray



DESCRIPTION

High quality primer spray for plastics treatment.

APPLICATION

The product is used as an adhesion promoter for almost all plastics, except for polyethylene.

CHARACTERISTICS

- Quick drying at room temperature
- Excellent adhesion to plastics
- Contains silver pigment for application control
- Can be overcoated with any waterborne and solvent-based topcoats

SUBSTRATES

Most of plastics, polyester putty, sanded G.R.P, old / OEM paintworks.

Articles	Description	Pcs. / pack
4-435-0400	1K Plastic Spray Primer, 400 ml	6

SUBSTRATE PRETREATMENT



Clean and degrease the plastic surface with C.A.R.FIT Silicone Remover. It is recommended to matt the surface and clean it again to improve adhesion

APPLICATION



Shake thoroughly for at least 2 minutes



Apply the primer in maximum 2 thin coats
Consumption: 1 spray can / ca. 2 – 3m²



Flash-off between layers: 3 – 5 min



Spraying distance: 25 – 30 cm
 · Apply at room temperature. Optimal application temperature: 15 – 25°C
 · Shake the spray can once more before application of each new coat
 · After use, hold aerosol can upside down and spray briefly to clean the nozzle

FURTHER TREATMENT



Air drying / 20°C
 Overcoat after: ca. 10 – 15 min
 Drying time depends on environment temperature, humidity and coating thickness



Apply subsequent materials according to plastic painting technology

TECHNICAL DATA

Basis	polyolefine resin
Colour	silver

STORAGE



This is a pressurized container, do not expose to direct sunlight or store above 35°C